

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : AMPRO Resin
Type of product : Epoxy resin
Product group : Resin

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Industrial/Professional use spec : None

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd
St Cross Business Park
Newport
PO30 5WU Isle of Wight - United Kingdom
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)
Regulatory@gurit.com - www.gurit.com

1.4. Emergency telephone number

Emergency number : Carechem 24: +44 (0) 1273 289451 24 Hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Skin corrosion/irritation, Category 2 H315
Serious eye damage/eye irritation, Category 2 H319
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 2 H411
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS07

GHS09

Signal word (CLP)

: Warning

Hazardous ingredients

: reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700); Formaldehyde, polymer with (chloromethyl)oxirane and phenol

Hazard statements (CLP)

: H315 - Causes skin irritation.
H317 - May cause an allergic skin reaction.
H319 - Causes serious eye irritation.
H411 - Toxic to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P261 - Avoid breathing vapours.
P264 - Wash hands thoroughly after handling.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.
P280 - Wear eye protection, protective clothing, protective gloves.

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	(CAS-No.) 1675-54-3 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	$\geq$ 50	Skin Irrit. 2, H315 Eye Irrit. 2, H319 Skin Sens. 1, H317 Aquatic Chronic 2, H411
Formaldehyde, polymer with (chloromethyl)oxirane and phenol	(CAS-No.) 9003-36-5 (EC-No.) 500-006-8 (REACH-no) 01-2119454392-40	10 - 25	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Acute Not classified Aquatic Chronic 2, H411
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	10 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319

Specific concentration limits:

Name	Product identifier	Specific concentration limits
reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700)	(CAS-No.) 1675-54-3 (EC-No.) 500-033-5 (EC Index-No.) 603-074-00-8 (REACH-no) 01-2119456619-26	(5 $\leq$ C < 100) Skin Irrit. 2, H315 (5 $\leq$ C < 100) Eye Irrit. 2, H319

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Wash skin with plenty of water. Take off contaminated clothing. If skin irritation or rash occurs: Get medical advice/attention.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
First-aid measures after ingestion	: Call a poison center or a doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Irritation. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Eye irritation.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire	: Toxic fumes may be released.
--	--------------------------------

5.3. Advice for firefighters

Protection during firefighting	: Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information	: Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures	: Ventilate spillage area. Avoid contact with skin and eyes. Avoid breathing vapours.
----------------------	---

6.1.2. For emergency responders

Protective equipment	: Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures	: Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

6.3. Methods and material for containment and cleaning up

For containment	: Collect spillage.
Methods for cleaning up	: Take up liquid spill into absorbent material.
Other information	: Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling	: Ensure good ventilation of the work station. Avoid contact with skin and eyes. Wear personal protective equipment. Avoid breathing vapours.
Hygiene measures	: Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions	: Store in a well-ventilated place. Keep cool.
Maximum storage period	: 2 year
Storage temperature	: ≤ 30 °C Storage at elevated temperatures may cause pressure build-up in sealed containers
Storage area	: Store away from heat. Store in a well-ventilated place.
Special rules on packaging	: Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Safety glasses.

Hand protection:					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)				EN ISO 374
Eye protection:					
Safety glasses					
Skin and body protection:					
Wear suitable protective clothing					
Type			Standard		
Tyvek® Gown/Coveralls			EN 13034		
Respiratory protection:					
In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended					
Device	Filter type		Condition		Standard
Disposable half mask	Gas/vapour filter		Vapour protection		EN 405

Personal protective equipment symbol(s):



AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Environmental exposure controls:

Avoid release to the environment.

Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless liquid.
Colour	: clear.
Odour	: characteristic.
Odour threshold	: No data available
pH	: ≈ 6
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: $> 93^{\circ}\text{C}$ Estimated on the basis of the constituents :
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20°C	: No data available
Relative density	: No data available
Density	: 1.16 g/cm^3
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: $456.034\text{ mm}^2/\text{s}$
Viscosity, dynamic	: $529\text{ cP } 25^{\circ}\text{C}$
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral)	: Not classified
Acute toxicity (dermal)	: Not classified
Acute toxicity (inhalation)	: Not classified

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) (1675-54-3)

LD50 oral rat	11400 mg/kg
---------------	-------------

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LD50 oral rat	> 10000 mg/kg
LD50 dermal rat	> 2000 mg/kg

benzyl alcohol (100-51-6)	
LD50 oral rat	1230 mg/kg
LD50 dermal rabbit	2 g/kg
LC50 inhalation rat (mg/l)	8.8 mg/l/4h

Skin corrosion/irritation	: Causes skin irritation. pH: $\approx$ 6
Serious eye damage/irritation	: Causes serious eye irritation. pH: $\approx$ 6
Respiratory or skin sensitisation	: May cause an allergic skin reaction.
Germ cell mutagenicity	: Not classified
Carcinogenicity	: Not classified
Reproductive toxicity	: Not classified
STOT-single exposure	: Not classified
STOT-repeated exposure	: Not classified
Aspiration hazard	: Not classified

AMPRO Resin	
Viscosity, kinematic	456.034 mm ² /s

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Toxic to aquatic life with long lasting effects.
Acute aquatic toxicity	: Not classified
Chronic aquatic toxicity	: Toxic to aquatic life with long lasting effects.

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)	
LC50 fish 1	1.5 mg/l
LC50 fish 2	2 mg/l

Formaldehyde, polymer with (chloromethyl)oxirane and phenol (9003-36-5)	
LC50 fish 1	< 1 mg/l

benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
EC50 72h algae (1)	700 mg/l

12.2. Persistence and degradability

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)	
Persistence and degradability	May cause long-term adverse effects in the environment.

12.3. Bioaccumulative potential

reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight $\leq$ 700) (1675-54-3)	
Bioaccumulative potential	Not established.

benzyl alcohol (100-51-6)	
Log Pow	1.1

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

12.6. Other adverse effects

No additional information available



SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
UN 3082	UN 3082	UN 3082
14.2. UN proper shipping name		
ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.	Environmentally hazardous substance, liquid, n.o.s.
Transport document description		
UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, (-)	UN 3082 ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III, MARINE POLLUTANT	UN 3082 Environmentally hazardous substance, liquid, n.o.s. (reaction product: bisphenol-A-(epichlorhydrin); epoxy resin (number average molecular weight ≤ 700) ; Formaldehyde, polymer with (chloromethyl)oxirane and phenol), 9, III
14.3. Transport hazard class(es)		
9	9	9
		
14.4. Packing group		
III	III	III
14.5. Environmental hazards		
Dangerous for the environment : Yes	Dangerous for the environment : Yes Marine pollutant : Yes	Dangerous for the environment : Yes

No supplementary information available

14.6. Special precautions for user

Overland transport


Classification code (ADR)	: M6
Special provisions (ADR)	: 274, 335, 375, 601
Limited quantities (ADR)	: 5I
Excepted quantities (ADR)	: E1
Packing instructions (ADR)	: P001, IBC03, LP01, R001

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Special packing provisions (ADR)	: PP1
Mixed packing provisions (ADR)	: MP19
Portable tank and bulk container instructions (ADR)	: T4
Portable tank and bulk container special provisions (ADR)	: TP1, TP29
Tank code (ADR)	: LGBV
Vehicle for tank carriage	: AT
Transport category (ADR)	: 3
Special provisions for carriage - Packages (ADR)	: V12
Special provisions for carriage - Loading, unloading and handling (ADR)	: CV13
Hazard identification number (Kemler No.)	: 90
Orange plates	:



Tunnel restriction code (ADR)	: -
EAC code	: •3Z

Transport by sea

Special provisions (IMDG)	: 274, 335, 969
Limited quantities (IMDG)	: 5 L
Excepted quantities (IMDG)	: E1
Packing instructions (IMDG)	: LP01, P001
Special packing provisions (IMDG)	: PP1
IBC packing instructions (IMDG)	: IBC03
Tank instructions (IMDG)	: T4
Tank special provisions (IMDG)	: TP2, TP29
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-F
Stowage category (IMDG)	: A

Air transport

PCA Excepted quantities (IATA)	: E1
PCA Limited quantities (IATA)	: Y964
PCA limited quantity max net quantity (IATA)	: 30kgG
PCA packing instructions (IATA)	: 964
PCA max net quantity (IATA)	: 450L
CAO packing instructions (IATA)	: 964
CAO max net quantity (IATA)	: 450L
Special provisions (IATA)	: A97, A158, A197
ERG code (IATA)	: 9L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

AMPRO Resin

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:

Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute Not classified	Hazardous to the aquatic environment - Acute Hazard Not classified
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Skin Irrit. 2	H315	Calculation method
Eye Irrit. 2	H319	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 2	H411	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Name : AMPRO CLR Slow Hardener
Type of product : Hardener (Crosslinker)
Product group : Hardener

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Intended for general public
Main use category : Industrial use, Professional use, Consumer use
Industrial/Professional use spec : None

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Gurit (UK) Ltd
St Cross Business Park
Newport
PO30 5WU Isle of Wight - United Kingdom
T +44 (0) 1983 828 000 (All Technical and Commercial Enquiries)
Regulatory@gurit.com - www.gurit.com

1.4. Emergency telephone number

Emergency number : Carechem 24: +44 (0) 1273 289451 24 Hours

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Acute toxicity (oral), Category 4 H302
Skin corrosion/irritation, Category 1B H314
Serious eye damage/eye irritation, Category 1 H318
Skin sensitisation, Category 1 H317
Hazardous to the aquatic environment — Chronic Hazard, Category 3 H412
Full text of H statements : see section 16

Adverse physicochemical, human health and environmental effects

Harmful if swallowed. Causes severe skin burns and eye damage. May cause an allergic skin reaction. Causes serious eye damage. Harmful to aquatic life with long lasting effects.

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP)



GHS05

GHS07

Signal word (CLP)

: Danger

Hazardous ingredients

: Propylene glycol diamine, 2-amino-, diether with Propylene; benzyl alcohol; 3-aminomethyl-3,5,5-trimethylcyclohexylamine; Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane; 1,3-Benzenedimethanamine; 1,6-Hexanediamine, 2,2,4(or 2,4,4)-trimethyl-; Phenol, styrenated

Hazard statements (CLP)

: H302 - Harmful if swallowed.
H314 - Causes severe skin burns and eye damage.
H317 - May cause an allergic skin reaction.
H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements (CLP)

: P102 - Keep out of reach of children.
P260 - Do not breathe vapours.
P264 - Wash hands thoroughly after handling.
P270 - Do not eat, drink or smoke when using this product.
P272 - Contaminated work clothing should not be allowed out of the workplace.
P273 - Avoid release to the environment.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

2.3. Other hazards

No additional information available

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
3-aminomethyl-3,5,5-trimethylcyclohexylamine	(CAS-No.) 2855-13-2 (EC-No.) 220-666-8 (EC Index-No.) 612-067-00-9 (REACH-no) 01-2119514687-32	25 - 50	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,3-Benzenedimethanamine	(CAS-No.) 1477-55-0 (EC-No.) 216-032-5 (REACH-no) 01-2119480150-50	10 - 25	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation:dust,mist), H332 Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
Propylene glycol diamine, 2-amino-, diether with Propylene	(CAS-No.) 9046-10-0 (REACH-no) 01-2119557899-12	10 - 25	Skin Corr. 1C, H314 Eye Dam. 1, H318 Aquatic Chronic 3, H412
Phenol, 4,4'-(1-methylethylidene)bis-, polymer with 5-amino-1,3,3-trimethylcyclohexanemethanamine and (chloromethyl)oxirane	(CAS-No.) 38294-64-3; 68609-08-5 (REACH-no) 01-2119965165-33	3 - 10	Skin Corr. 1B, H314 Skin Sens. 1, H317 Aquatic Chronic 3, H412
1,6-Hexanediamine, 2,2,4(or 2,4,4)-trimethyl-	(CAS-No.) 25513-64-8 (EC-No.) 247-063-2 (REACH-no) 01-2119560598-25	1 - 5	Acute Tox. 4 (Oral), H302 Skin Corr. 1A, H314 Eye Dam. 1, H318 Skin Sens. 1, H317
benzyl alcohol	(CAS-No.) 100-51-6 (EC-No.) 202-859-9 (EC Index-No.) 603-057-00-5 (REACH-no) 01-2119492630-38	10 - 5	Acute Tox. 4 (Oral), H302 Acute Tox. 4 (Dermal), H312 Acute Tox. 4 (Inhalation), H332 Eye Irrit. 2, H319
Phenol, styrenated	(CAS-No.) 61788-44-1 (EC-No.) 262-975-0	< 3	Skin Irrit. 2, H315 Skin Sens. 1, H317 Aquatic Chronic 2, H411

Full text of H-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Call a physician immediately.
First-aid measures after inhalation	: Remove person to fresh air and keep comfortable for breathing.
First-aid measures after skin contact	: Rinse skin with water/shower. Take off immediately all contaminated clothing. Call a physician immediately.
First-aid measures after eye contact	: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Call a physician immediately.
First-aid measures after ingestion	: Rinse mouth. Do not induce vomiting. Call a physician immediately.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after skin contact	: Burns. May cause an allergic skin reaction.
Symptoms/effects after eye contact	: Serious damage to eyes.
Symptoms/effects after ingestion	: Burns.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Water spray. Dry powder. Foam. Carbon dioxide.
Unsuitable extinguishing media	: Do not use a heavy water stream.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

5.2. Special hazards arising from the substance or mixture

Hazardous decomposition products in case of fire : Toxic fumes may be released.

5.3. Advice for firefighters

Precautionary measures fire : Evacuate area.
Firefighting instructions : Exercise caution when fighting any chemical fire.
Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.
Other information : Collect contaminated fire fighting water separately. It must not enter drains.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Protective equipment : Protective clothing.
Emergency procedures : Ventilate spillage area. Avoid contact with skin and eyes. Do not breathe vapours.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".
Emergency procedures : Ventilate area.

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Collect spillage.
Methods for cleaning up : Take up liquid spill into absorbent material.
Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13. For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Avoid contact with skin and eyes. Do not breathe vapours. Wear personal protective equipment.
Hygiene measures : Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. Do not eat, drink or smoke when using this product. Always wash hands after handling the product. Separate working clothes from town clothes. Launder separately. Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store locked up. Store in a well-ventilated place. Keep cool.
Storage temperature : ≤ 30 °C Possible pressure build-up
Storage area : Store away from heat. Store in a well-ventilated place.
Special rules on packaging : Keep only in original container.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

No additional information available

8.2. Exposure controls

Appropriate engineering controls:

Ensure good ventilation of the work station.

Personal protective equipment:

Safety glasses.

Hand protection:					
Protective gloves					
Type	Material	Permeation	Thickness (mm)	Penetration	Standard
Disposable gloves	Nitrile rubber (NBR)				EN ISO 374
Eye protection:					
Safety glasses					

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Skin and body protection:			
Wear suitable protective clothing			
Type		Standard	
Tyvek® Gown/Coveralls		EN 13034	
Respiratory protection:			
In case of insufficient ventilation, wear suitable respiratory equipment. Where exposure through inhalation may occur from use, respiratory protection equipment is recommended			
Device	Filter type	Condition	Standard
Disposable half mask	Gas/vapour filter	Vapour protection	EN 405

Personal protective equipment symbol(s):



Environmental exposure controls:

Avoid release to the environment.

Other information:

Industrial and professional. Perform risk assessment prior to use. Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Clear to pale yellow liquid.
Colour	: clear.
Odour	: Amine-like.
Odour threshold	: No data available
pH	: No data available
Relative evaporation rate (butylacetate=1)	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability (solid, gas)	: Not applicable
Vapour pressure	: No data available
Relative vapour density at 20 °C	: No data available
Relative density	: No data available
Solubility	: No data available
Log Pow	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosive properties	: No data available
Oxidising properties	: No data available
Explosive limits	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

The product is non-reactive under normal conditions of use, storage and transport. Product is not explosive.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

10.4. Conditions to avoid

None under recommended storage and handling conditions (see section 7).

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity (oral) : Harmful if swallowed.

Acute toxicity (dermal) : Not classified

Acute toxicity (inhalation) : Not classified

ATE CLP (oral)	1001.768 mg/kg bodyweight
----------------	---------------------------

Propylene glycol diamine, 2-amino-, diether with Propylene (9046-10-0)

LD50 oral rat	2885 mg/kg
---------------	------------

LD50 dermal rabbit	2980 mg/kg
--------------------	------------

benzyl alcohol (100-51-6)

LD50 oral rat	1230 mg/kg
---------------	------------

LD50 dermal rabbit	2 g/kg
--------------------	--------

LC50 inhalation rat (mg/l)	8.8 mg/l/4h
----------------------------	-------------

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)

LD50 oral rat	1030 mg/kg
---------------	------------

LD50 dermal rat	> 2000 mg/kg
-----------------	--------------

LC50 inhalation rat (Dust/Mist - mg/l/4h)	5.01 mg/l/4h
---	--------------

1,3-Benzenedimethanamine (1477-55-0)

LD50 oral	930 (≤ 1180) mg/kg
-----------	--------------------

LD50 dermal rat	2000 mg/kg
-----------------	------------

LD50 dermal rabbit	> 3100 mg/kg
--------------------	--------------

LC50 inhalation rat (Dust/Mist - mg/l/4h)	1.34 mg/l/4h
---	--------------

Phenol, styrenated (61788-44-1)

LD50 oral rat	2500 mg/kg
---------------	------------

LD50 dermal rabbit	> 7940 mg/kg
--------------------	--------------

Skin corrosion/irritation : Causes severe skin burns and eye damage.

Serious eye damage/irritation : Causes serious eye damage.

Respiratory or skin sensitisation : May cause an allergic skin reaction.

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

STOT-single exposure : Not classified

STOT-repeated exposure : Not classified

Aspiration hazard : Not classified

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general : Harmful to aquatic life with long lasting effects.

Acute aquatic toxicity : Not classified

Chronic aquatic toxicity : Harmful to aquatic life with long lasting effects.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

benzyl alcohol (100-51-6)	
LC50 fish 1	460 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 Daphnia 1	23 mg/l (Exposure time: 48 h - Species: water flea)
EC50 72h algae (1)	700 mg/l

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
EC50 Daphnia 1	14.6 - 21.5 mg/l (48 h - Species: Daphnia magna [semi-static])
EC50 72h algae (1)	37 mg/l (Species: Desmodesmus subspicatus)

1,3-Benzenedimethanamine (1477-55-0)	
EC50 72h algae (1)	12 mg/l

12.2. Persistence and degradability

No additional information available

12.3. Bioaccumulative potential

benzyl alcohol (100-51-6)	
Log Pow	1.1

3-aminomethyl-3,5,5-trimethylcyclohexylamine (2855-13-2)	
Log Pow	0.79 (at 23 °C)

Phenol, styrenated (61788-44-1)	
Log Pow	> 4 (at 22 °C)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

No additional information available

12.6. Other adverse effects

No additional information available

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Regional legislation (waste)	: Disposal must be done according to official regulations.
Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Product/Packaging disposal recommendations	: Avoid release to the environment. Dispose in a safe manner in accordance with local/national regulations.
Ecology - waste materials	: Avoid release to the environment.
European List of Waste (LoW) code	: 08 04 09* - waste adhesives and sealants containing organic solvents or other dangerous substances

SECTION 14: Transport information

In accordance with ADR / IATA / IMDG

ADR	IMDG	IATA
14.1. UN number		
UN 2735	UN 2735	UN 2735
14.2. UN proper shipping name		
POLYAMINES, LIQUID, CORROSIVE, N.O.S.	POLYAMINES, LIQUID, CORROSIVE, N.O.S.	Polyamines, liquid, corrosive, n.o.s.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Transport document description		
UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 1,3-Benzenedimethanamine), 8, II, (E)	UN 2735 POLYAMINES, LIQUID, CORROSIVE, N.O.S. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 1,3-Benzenedimethanamine), 8, II	UN 2735 Polyamines, liquid, corrosive, n.o.s. (3-aminomethyl-3,5,5-trimethylcyclohexylamine ; 1,3-Benzenedimethanamine), 8, II
14.3. Transport hazard class(es)		
8	8	8
		
14.4. Packing group		
II	II	II
14.5. Environmental hazards		
Dangerous for the environment : No	Dangerous for the environment : No Marine pollutant : No	Dangerous for the environment : No
No supplementary information available		
14.6. Special precautions for user		

Overland transport

Classification code (ADR)	: C7
Special provisions (ADR)	: 274
Limited quantities (ADR)	: 1I
Excepted quantities (ADR)	: E2
Packing instructions (ADR)	: P001, IBC02
Mixed packing provisions (ADR)	: MP15
Portable tank and bulk container instructions (ADR)	: T11
Portable tank and bulk container special provisions (ADR)	: TP1, TP27
Tank code (ADR)	: L4BN
Vehicle for tank carriage	: AT
Transport category (ADR)	: 2
Hazard identification number (Kemler No.)	: 80
Orange plates	:



Tunnel restriction code (ADR)	: E
EAC code	: 2X
APP code	: B

Transport by sea

Special provisions (IMDG)	: 274
Packing instructions (IMDG)	: P001
IBC packing instructions (IMDG)	: IBC02
Tank instructions (IMDG)	: T11
Tank special provisions (IMDG)	: TP1, TP27
EmS-No. (Fire)	: F-A
EmS-No. (Spillage)	: S-B
Stowage category (IMDG)	: A
Segregation (IMDG)	: SG35

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

Properties and observations (IMDG) : Colourless to yellowish liquids or solutions with a pungent odour. Miscible with or soluble in water. When involved in a fire, evolve toxic gases. Corrosive to most metals, especially to copper and its alloys. Reacts violently with acids. Cause burns to skin, eyes and mucous membranes.

Air transport

PCA Excepted quantities (IATA) : E2
PCA Limited quantities (IATA) : Y840
PCA limited quantity max net quantity (IATA) : 0.5L
PCA packing instructions (IATA) : 851
PCA max net quantity (IATA) : 1L
CAO packing instructions (IATA) : 855
CAO max net quantity (IATA) : 30L
Special provisions (IATA) : A3, A803
ERG code (IATA) : 8L

14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no substance on the REACH candidate list

Contains no REACH Annex XIV substances

Contains no substance subject to REGULATION (EU) No 649/2012 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

No additional information available

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Full text of H- and EUH-statements:	
Acute Tox. 4 (Dermal)	Acute toxicity (dermal), Category 4
Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Chronic 2	Hazardous to the aquatic environment — Chronic Hazard, Category 2
Aquatic Chronic 3	Hazardous to the aquatic environment — Chronic Hazard, Category 3
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
Eye Irrit. 2	Serious eye damage/eye irritation, Category 2
Skin Corr. 1A	Skin corrosion/irritation, Category 1A
Skin Corr. 1B	Skin corrosion/irritation, Category 1B
Skin Corr. 1C	Skin corrosion/irritation, Category 1C
Skin Irrit. 2	Skin corrosion/irritation, Category 2
Skin Sens. 1	Skin sensitisation, Category 1
H302	Harmful if swallowed.
H312	Harmful in contact with skin.
H314	Causes severe skin burns and eye damage.
H315	Causes skin irritation.

AMPRO CLR Slow Hardener

Safety Data Sheet

according to Regulation (EC) No. 1907/2006 (REACH) with its amendment Regulation (EU) 2015/830

H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H411	Toxic to aquatic life with long lasting effects.
H412	Harmful to aquatic life with long lasting effects.

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:		
Acute Tox. 4 (Oral)	H302	Calculation method
Skin Corr. 1B	H314	Calculation method
Eye Dam. 1	H318	Calculation method
Skin Sens. 1	H317	Calculation method
Aquatic Chronic 3	H412	Calculation method

SDS EU (REACH Annex II)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product. The information contained within this document is Gurit copyright and any distribution or publication beyond the recipient's organisation is prohibited without Gurit's prior written consent.